

## TECHNICAL DATASHEET

# Masterbatch White QMB-001W

### PRODUCT DESCRIPTION

**QMB-001W** is a general-purpose white PE masterbatch for all kinds of extruded and moulded plastics. It has good dispersion resulting in an efficient hiding power and easy processing.

### TYPICAL APPLICATIONS

Plastic Extrusion.

### RECOMMENDED USAGE

Additional recommendations can be provided by our Technical Department.

### TYPICAL PROPERTY VALUES

PROPERTY	UNIT	VALUE RANGE	METHOD
Specific Density	g/cm <sup>3</sup>	1.890 - 1.950	ASTM D792
Melt Flow Rate (190°C, 2.16Kg)	g/10 min	8.00 – 13.00	ASTM D1238
Moisture Content	%	< 0.06	In-house Method
Titanium Dioxide	%	39 - 42	In-house Method

*The above properties represent typical laboratory data and are subjected to change. This information should be used as a reference only.*

### PACKING

White pellet form, packed in PE bags of 25Kg each.

### STORAGE AND HANDLING

Not to exceed 12 months. Storage in very humid areas or under direct sunlight should be avoided.

### SAFETY

Not classified as hazardous material.

### RECYCLING

This product can be recycled using current methods of shredding and cleaning. Production waste should be properly segregated and kept clean to facilitate direct recycling.

# MASTER BATCH

QMB-001W